

I. Amendments to the Specification

Please replace the specification with the following. A clean version of the amended specification is enclosed as Attachment A.

A SEAT-BELT BUCKLE ARRANGEMENT

CROSS REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to PCT/SE2003/001111, filed June 26, 2003, GB 0216900.1, filed July 19, 2002, and GB 0301965.0, filed January 28, 2003.

BACKGROUND OF THE INVENTION

[0002] ~~THE PRESENT INVENTION~~ The present invention relates to a seat belt buckle assembly and more particularly relates to a seat belt buckle assembly for use as part of a seat belt arrangement in a motor vehicle such as a motor car.

[0003] A seat belt buckle must be located, within a motor vehicle, at a position where it may easily be found by an occupant of a vehicle attempting to fasten a safety belt in position, but the buckle should not be obtrusive.

[0004] Many seat belt buckle assemblies have been proposed previously, ~~to be mounted in position within~~ for use in a motor vehicle. A typical buckle assembly incorporates an element extending from the buckle to an end piece or mounting plate, ~~the plate. The~~ being is end piece or mounting plate ~~being is~~ provided with an aperture so that the end piece or mounting plate may be readily bolted to an anchor point provided within a motor vehicle. The seat-belt buckle is itself a component which is

configured to receive releasably a tongue or latch plate which is mounted on the seat-belt. Typically the seat-belt buckle receives the tongue through a slot or opening formed in the ~~buckle, and when~~ buckle. When the tongue is inserted into the buckle, the tongue is automatically retained within the buckle. The tongue can be released from the buckle by depressing an appropriate actuating button.

[0005] There is, in some cases, a requirement for a very compact or small buckle assembly, especially where the buckle is to be positioned extremely close to the anchoring point. However when the buckle is intended for use with a safety-belt provided on a rear seat of a motor vehicle, the buckle must be spaced from the anchoring point.

[0006] Seat-belt buckles that are utilised on rear seats are often located at the point where the squab or seat cushion of the rear seat meets with the back-rest of the rear seat. The buckle should have an initial position in which the buckle is not obtrusive, especially if the rear seat is to accommodate three ~~passengers,~~ passengers to enable the passenger who is to have the middle position to slide across the seat without any uncomfortable engagement with the seat-belt buckle. However, it is appropriate for the buckle to have a more protruding position when the buckle is in use.

[0007] The present invention seeks to provide an improved buckle assembly.

SUMMARY OF THE INVENTION

[0008] According to one aspect of this invention there is provided seat belt buckle assembly, ~~the assembly having:~~ having a webbing strap, an end piece defining a slot to receive the webbing strap and a ~~buckle, the~~ buckle. The buckle ~~having~~ has a slot to receive the webbing ~~strap; the~~ strap. The webbing strap ~~having~~

has a first portion extending through the slot in the end piece and is secured to the main part of the webbing strap and a second portion passing through the slot in the buckle and secured to the main part of the webbing ~~strap, one said~~ strap. ~~One~~ portion ~~being~~ is stitched directly to the main part of the webbing strap and the other portion being stitched to the combination of ~~said~~ one portion and the main part of the strap, with stitching passing through the main part and the two portions of the strap.

[0009] Preferably, the slot in the end piece and the slot in the buckle each have a width less than the width of the ~~strap, strap with~~ portions of the strap being tucked in the region of each ~~slot, the~~ slot. The stitching ~~connecting~~ connects the ~~said~~ other portion to the combination of the first end portion and the main region of the strap ~~extending~~ extends only through three super-imposed layers of strap.

[0010] Conveniently, the stitching securing the ~~said~~ other portion to the combination of the first end portion and the main part of the strap is of rhombic form.

[0011] The buckle assembly may further comprise a connector, the connector having an elongate element and at least one mounting element connected to or formed integrally with the elongate element for pivotal movement relative to the elongate ~~element, the or each mounting element being~~ element. ~~One or more of the mounting elements is~~ resiliently biased to a predetermined position relative to the elongate element, or each mounting element ~~being~~ is mounted on the ~~buckle, the said buckle. The~~ second portion of the strap ~~passing~~ passes around at least part of the connector, ~~and~~ where it is superimposed over the main part of the strap, ~~being~~ and secured thereto so that the superimposed regions of the strap embrace the ~~said~~ elongate element.

[0012] Preferably, said the resilient bias between ~~the or each mounting element~~ one or more of the mounting elements and the elongate element is effective to move the buckle to an initial position in which the axis of the buckle is substantially perpendicular to the axis of the elongate element.

[0013] Conveniently, said the resilient bias is effected by at least one resilient biasing element.

[0014] Preferably the elongate element is formed of metal ~~sheet,~~ sheet with one end of the elongate element forming a loop which receives a rod which is pivotal relative to the elongate ~~element,~~ the element. The rod extending extends to and ~~being~~ is connected to arms which extend from part of the mounting ~~element,~~ the element. The mounting element being is constituted by a mounting ~~plate,~~ there being plate with at least one resilient biasing element engaging the elongate element and a ~~said~~ an arm to impart said the bias to the mounting element.

[0015] Preferably ~~the or each said~~ one or more resilient biasing ~~element~~ elements comprises a helical spring surrounding said the rod.

[0016] Conveniently, said the connector defines the slot present in the buckle.

[0017] In an alternative embodiment, ~~the, or each, mounting element~~ one or more mounting elements and the elongate element are each formed from a single length of bent resilient wire.

[0018] Preferably, the elongate element is defined by an elongate loop of said the wire extending between a pair of hook-shaped ~~formations,~~ each said formations. Each hook-shaped formation defining a respective mounting element for engagement with the buckle.

[0019] Conveniently, the region of said the wire forming the elongate element, and the region of said the wire forming ~~the, or each, mounting element~~ one or more

of the mounting elements are joined by a, ~~or a respective,~~ helically wound region of ~~said wire, the~~ the wire. The helically wound region of wire providing ~~said the~~ resilient bias between ~~the, or each, mounting element~~ one or more of the mounting elements and the elongate element.

[0020] Advantageously, ~~said the~~ second portion of the strap passes through an aperture in the buckle and around ~~said the or each mounting element~~ one or more of the mounting elements.

[0021] According to another aspect of this invention, there is provided a method of assembling a seat belt buckle assembly having a webbing strap, an end piece defining a slot to receive the webbing strap and a buckle defining a slot to receive the webbing ~~strap, the~~ strap. The method comprising the steps of: of passing one end portion of the strap through the slot in the end ~~piece, piece,~~ passing the other end portion of the strap through the slot in the ~~buckle, buckle,~~ securing a first end portion of the strap to the main part of the strap using stitching and subsequently securing the second end portion of the strap to the combination of ~~the~~ one end of the strap and the main piece of the strap using stitching, and the stitching passing through the main part and the two portions of the strap.

[0022] Preferably, the strap is wider than each of ~~said slots,~~ the slots and the method comprises the steps of tucking in parts of the strap adjacent each slot and performing the first stitching in a region where there are only two super-imposed layers of strap and performing the second stitching in a region where there are three super-imposed layers of strap.

[0023] Conveniently, ~~said the~~ first end of the strap is passed through the slot in the end piece and the other end of the strap is passed through the slot in the buckle.

[0024] Preferably after superimposing ~~said~~ one portion and the main body portion of the strap, the adjacent edges of the superimposed strap portions are secured together to define a central pocket, ~~and the pocket.~~ pocket. The method includes the step of inserting an elongate element of a connector into the pocket, superimposing the other portion of the strap over at least part of the main body portion of the strap, and securing the said other end portion of the strap to the said main body portion of the strap to embrace the elongate element.

BRIEF DESCRIPTION OF THE DRAWINGS

[0025] In order that the invention may be more readily understood, and so that further features thereof may be appreciated, the invention will now be described, by way of example, with reference to the accompanying drawings in which:

[0026] ~~FIGURE~~ Figure 1 is a view of a webbing strap and an end piece;

[0027] ~~FIGURE~~ Figure 2 is a view of the webbing strap and end piece when secured to a seat belt buckle.

[0028] ~~FIGURE~~ Figure 3 is a perspective view of an anchoring plate forming part of a seat-belt buckle arrangement in accordance with the invention,

[0029] ~~FIGURE~~ Figure 4 is a diagrammatic view of a length of webbing,

[0030] ~~FIGURE~~ Figure 5 is a perspective view of a connector,

[0031] ~~FIGURE~~ Figure 6 is a diagrammatic view of a buckle,

[0032] ~~FIGURE~~ Figure 7 is a view showing a first stage in the assembly of an example of a buckle arrangement in accordance with the invention, illustrating the anchoring plate and part of the strap,

[0033] ~~FIGURE~~ Figure 8 is a view corresponding to Figure 7 showing a subsequent stage during the manufacture of the buckle arrangement showing the anchoring plate, the strap and the connector,

[0034] ~~FIGURE~~ Figure 9 is a view corresponding to Figure 8 showing a further stage during the assembly of the buckle arrangement,

[0035] ~~FIGURE~~ Figure 10 is a view which is a slightly schematic side illustration of the completed buckle assembly, illustrating the assembly in two alternate conditions,

[0036] ~~FIGURE~~ Figure 11 is a perspective view of a connector forming part of an alternative embodiment of the present invention,

[0037] ~~FIGURE~~ 12 is a longitudinal sectional view through a buckle, illustrating the buckle connected to the connector illustrated in Figure 9,

[0038] ~~FIGURE~~ Figure 13 is a view showing a subsequent stage in the assembly of the alternative buckle arrangement showing the anchor plate, the strap, the connector and the buckle,

[0039] ~~FIGURE~~ Figure 14 is a view corresponding to Figure 13 showing a subsequent stage in the assembly of the buckle, and

[0040] ~~FIGURE~~ Figure 15 is a view corresponding generally to that of Figure 12, but illustrating the fully assembled buckle assembly, and

~~FIGURE 16 is a view corresponding generally to Figure 15, illustrating the assembly in an alternate position.~~

DETAILED DESCRIPTION OF THE INVENTION

[0041] Referring initially to Figure 1 of the accompanying drawings, an end piece 1 is provided. The end piece 1 may be formed as a metal plate. Part of the metal plate defines an aperture or bolt hole 2 by means of which the end piece 1 may be secured to an appropriate anchoring point within a vehicle. The end piece 1 defines a further portion 3 provided with an oval slot 4. The slot 4, as will become clear from the following description, is intended to receive an end part of a webbing strap.

[0042] A webbing strap 5 is provided, of elongate form. The strap 5 has a width which is greater than the length of the slot 4.

[0043] One end 6 of the webbing strap 5 may be passed through the slot 4, side edge regions 7 of the belt being tucked inwardly, as indicated in phantom, ~~7~~, so that the relatively wide strap 5 may be accommodated within the relatively short slot 4. The end ~~piece~~ 6 of the strap 5 is super-imposed over the main region of the strap adjacent the end piece 1. The super-imposed regions are stitched using a square stitching pattern 8.

[0044] Subsequently the other end 9 of the strap 5 is passed through a slot (not shown) having a configuration similar to the slot 4, provided within a seat belt buckle 10 as shown in Figure 2.

[0045] Again, due to the relationship between the width of the strap 5 and the length of the slot in the buckle 10, edge portions of the strap 5 have to be tucked inwardly, as indicated in phantom, 11. The end ~~piece~~ 9 of the strap 5, after passing through the slot in the buckle ~~5~~ 10, is then super-imposed over the stitching 8 12. Further stitching is then carried out, the stitching 12 only being effected in the region where there are three super-imposed layers of strap 5, that is to say, with the

stitching 12 not being effected in the region where strap 5 is tucked in as shown in phantom of 7 and 11. A rhombic stitching pattern for stitching 12 may be utilised.

[0046] The stitching 12 is located completely between the buckle 10 and the end piece 1.

[0047] A buckle assembly is thus fabricated, the buckle assembly being very short. Thus the distance between the buckle 10 and the end piece 1 is minimal.

[0048] Referring now to Figures 3 to 10 of the accompanying drawings, a further embodiment of the invention will be described.

[0049] Figure 3 shows an end piece in the form of an anchor plate 24 21 formed of a metal strip. One end of the anchor plate 21 is provided with an anchoring aperture 22 adapted to receive a fastening bolt to secure the anchor plate 21 to an anchoring point within a motor vehicle. The other end of the anchor plate 21 is provided with a mounting aperture in the form of an elongate slot 23 dimensioned to receive part of a webbing strap.

[0050] Figure 4 is a diagrammatic view illustrating a length of webbing strap 24. The webbing strap 24 is of uniform width along its length.

[0051] Figure 5 illustrates a connector unit 25. The connector unit 25 comprises an elongate element in the form of a substantially rigid finger 26 formed, for example, of metal sheet. One end of the finger 26 is provided with a socket 27, which in the embodiment illustrated is formed by folding an end part of the finger 6 to form a closed loop. The socket 27 receives a transversely extending rod 28 which is rotatable within the socket 27. The opposed ends of the rod 28 are connected to two arms 29, 30 which extend from a mounting element in the form of a mounting plate 31. The mounting plate 31 has two apertures 32, 33 formed therein to facilitate the mounting of a safety-belt buckle to the mounting plate 31 as will be described

hereinafter. A relatively large slot or aperture 34 is formed defined between the plate 31, the arms 29, 30 and the rod 28. As will be described below, the mounting plate 44 31 is to be made fast with a buckle, so that the slot 34 is a slot present on the complete buckle dimensioned to receive the strap 24.

[0052] Two resilient biasing elements in the form of biasing springs 35 are provided which serve to bias the mounting plate 31 to a predetermined angular orientation relative to the finger 26. In the illustrated embodiment, each spring 35 comprises a helical spring which surrounds the rod 28. Each spring 35 is provided with a terminally extending portion at each end thereof, one extending portion of each spring 35 engaging the finger 26, and the other extending portion of each spring 35 engaging the arms 29, 30. Other forms of biasing ~~spring~~ springs may be utilised.

[0053] Turning now to Figure 6, a buckle 36 is illustrated. The buckle 36 has a housing 37 which defines, at one end, a slot 38 (which is not visible in Figure 6) by means of which a tongue may be inserted into the buckle 36. The buckle 36 includes a depressable button ~~37~~ 39 which may be depressed to release the tongue. The buckle 36 may be of a conventional design. The buckle 36, as will become clear from the following ~~description~~ description, is intended to be mounted on the above-described mounting plate 31.

[0054] Figure 5 7 illustrates an initial stage in the assembly of a buckle assembly in accordance with the present invention. Initially, a first end 40 of the webbing strap 24 is passed through the elongate slot 23 provided on the anchor plate 21, after which the end 40 of the webbing strap is moved to lie adjacent the main body part of the webbing strap 24. The first end 40 of the webbing strap 24 is then secured to the main body part of the strap 24 by means of two lines of

stitching ~~41, 42~~ 41 and 42 adjacent the super-imposed side edges of the strap 24. Thus the stitching 41 and 42 defines a central recess or “pocket” defined between the first end part 40 of the strap 24 and the main body part of the strap 24, in the area located between the two lines of stitching 41 and 42.

[0055] Subsequently the finger 26 of the mounting unit 25 is inserted into the pocket between the two lines of stitching 41 and 42 so that the mounting plate 31 lies over part of the strap 24, as shown in Figure 8.

[0056] Subsequently, as shown in Figure 9, the other second end part 43 of the webbing strap 24 is threaded around the rod 28 and the springs 35 of the connector unit 25 and through the aperture 34 defined between the mounting plate 31, the arms ~~29, 30~~ 29 and 30 and the rod 28. The second end part 43 of the webbing strap 24 is then located to overlie part of the main portion of the strap 24, and also part of the already stitched first end part 40 of the strap 24. Further stitching ~~44, 45~~ 44 and 45 is used to secure the second end part 43 of the strap in position, some of the stitching ~~44, 45~~ 44 and 45 passing only through the second end part 43 of the strap and the main part of the strap 24, and some of the stitching ~~44, 45~~ 44 and 45 passing through the second end part 43 of the strap 24, the first end part 40 of the strap 24 and the main body of the strap. The stitching serves to embrace the finger 26 within the sewn strap 24. The mounting plate 31 projects beyond the end of the stitched strap 24.

[0057] The mounted plate 31 may be mounted to the rest of the buckle 36 in the manner shown in Figure 10 using rivets or the like passing through the apertures 32 and 33 in the mounting plate 31 which engage corresponding apertures formed in the housing 37 of the buckle 36. In Figure 10 the location of the strap 24 and the location of the stitching is shown diagrammatically to facilitate an understanding of

the location of the relevant portions of the strap 24. However, it can be seen that the strap 24 passes through the slot 34 present on the completed buckle 36.

[0058] The biasing springs 35 serve to bias the mounting plate 31 towards an initial position in which the mounting plate 31 is substantially perpendicular to the axis of the finger 26. Thus the buckle 36 initially has the position shown in solid lines in Figure 10 in which the axis of the buckle 36 is substantially perpendicular to the axis of the finger 26. However, the buckle 36 can be moved, against the bias of the spring 35 to the alternate position shown in phantom in Figure 10, in which the buckle 36 is generally in alignment with the finger 26, extending substantially upwardly above the finger 26.

[0059] It is to be appreciated that a buckle assembly of the type described with reference to Figures 3 to 10 may be of particular use for mounting on the rear seat of a motor vehicle. The anchor plate 21 will pass through a gap provided at the back of the squab or seat cushion of the seat and beneath the back-rest of the seat, so that an appropriate bolt may pass through the anchoring aperture 22 to engage with an anchoring point formed on the body of the vehicle located beneath and behind the rear seat. The anchor plate 21 will extend part-way up through the gap between the squab and the back-rest of the seat, and the webbing strap 24, effectively reinforced by the finger 26, will extend up from the anchor plate 21 to a position adjacent the top of the squab of the rear seat. The buckle 36 will initially lie in a substantially ~~vertical~~ horizontal position in which the buckle 36 is unobtrusive, and will not impede a passenger attempting to slide across the rear seat to a central position in the rear seat. For example, the buckle 36 could be initially received within a recess provided in the back-rest of the rear seat. However, the buckle 36 is held ready for use and is easily accessible. When the buckle 36 is to be used, the buckle

36 is grasped and is pulled upwardly, causing the rod 28 to pivot within the socket 27, against the bias the springs 35, until the buckle 36 is substantially in the position shown in phantom in Figure 10. A tongue of a safety-belt may then easily be located within the buckle 36. When the buckle 36 is no longer in use, the spring-bias provided by the springs 35 will return the buckle 36 to the initial unobtrusive position shown in solid lines in Figure 10.

[0060] Turning now to consider Figures 11 to 16, a buckle assembly in accordance with an alternative embodiment of the present invention will now be described.

[0061] The alternative buckle assembly again comprises an anchor plate 21 and strap 24 substantially identical to those illustrated in Figures 3 and 4. However, as will be clear from Figures 11 to 16, the connector 50 of the alternative arrangement differs significantly from the connector 25 of the arrangement illustrated in Figures 3 to 10. The connector 50 illustrated in Figure 11 is fabricated from a single length of resiliently deformable metal wire 51. The length of metal wire 51 is illustrated as having been bent and deformed into a configuration which defines a pair of mounting elements 52 and an elongate element 53. Each mounting element 52 takes the form of a loop or hook of wire 54 terminating with an inwardly-turned free end 55 of the wire 51. The loop 54 of each mounting element 52 extends to a respective helically-wound length of wire 56, from which the wire 51 is formed into an elongate loop defining the elongate element 53. As illustrated in Figure 11, the two helically-wound lengths of wire 56 extend inwardly from the respective loops 54 such that the elongate element 53 is located between the two mounting elements 52.

[0062] As will therefore be appreciated, the connector 50 illustrated in Figure 11 is configured such that the two mounting elements 52 are formed integrally with the elongate element 53, which is in contrast to the connector 25 illustrated in Figure 5, in which the mounting element 50 is connected to a separate elongate element 24.

[0063] The helically-wound lengths of wire 56 serve generally the same purpose as the helical springs 35 of the connector 25 illustrated in Figure 5, in that each helically-wound length of wire 56 provides a degree of resilient bias between the mounting elements 52 and the elongate element 53, whilst permitting pivotal movement of the elongate element 53 about a notional axis relative to the mounting elements 52, against said the bias. In its relaxed state (illustrated most clearly in Figure 12), the connector 50 is configured such that the mounting elements 52 extend substantially perpendicularly with respect to the elongate element 53.

[0064] Figure 12 also illustrates, in longitudinal section, the buckle 57 of this alternative arrangement. The buckle 57 again comprises a housing 58 which defines, at one end, a slot 59 by means of which a tongue may be inserted into the buckle 57. The buckle 57 again includes a depressable button (not shown) which may be depressed to release the tongue.

[0065] Additionally, the housing 58 of the buckle 57 of this arrangement is provided with a slot or end 60 at the opposite end to the tongue-receiving slot 59, the slot 60 providing access to a longitudinal channel 61 which extends toward first under-surface-slot 62 provided transversely in the underside of the housing 58. At a position between the first under-surface-slot 62 and the end of the housing 58 opposite to the tongue-receiving slot 59, there is provided a second transverse

under-surface-slot 63 in the under-surface of the housing 58, the second slot 63 also communicating with the channel 61.

[0067] As also illustrated in Figure ~~10~~ 12, the slots ~~62, 63~~ 62 and 63 provided in the under-surface of the housing 58, together with the length of channel 61 therebetween, allow connection of the buckle 57 to the connector 50. The wire loops 50 of each mounting element 52 extend into the channel 61 through the first under-surface-slot 62, and extend along the channel 61 to exit the channel 61 through the second under-surface-slot 63, such that the inwardly-directed terminal ends 65 of the wire 61 bear against the under-surface of the housing 58 to retain the mounting element 52 in position.

[0068] Figure 13 illustrates a subsequent stage in the assembly of the alternative buckle assembly, which follows a stage of assembly substantially identical to that illustrated in Figure 7, in which a first end 40 of the webbing strap 24 is passed through the elongate slot 23 provided on the anchor plate 21, after which the end 40 of the webbing strap 24 is moved to lie adjacent to the main body part of the webbing strap 24, and is secured to the main body part of the webbing strap 24 by means of two lines of stitching ~~41, 42~~ 41 and 42 adjacent the super-imposed side edges of the strap 24. Figure 13 illustrates insertion of the elongate loop 53 of the connector 50 (which is already connected to the buckle 57) into the pocket defined between the two lines of stitching ~~40, 41~~ 41 and 42 so that the connector 50 and the buckle 57 lie over part of the strap 24.

[0069] Subsequently, as shown in Figure 14, the other second end 43 of the webbing strap 24 is threaded through the channel 61 via the first under-surface-slot 62, so as to exit the housing 58 of the buckle 57 through the end slot 60. The end part 43 of the webbing strap 24 is then located to overlie part of the main portion of

the strap 24, and also part of the already stitched first end part 40 of the strap 24. Further stitching ~~44, 45~~ 44 and 45 is again used to secure the second end part of the strap 43 in position, with some of the stitching ~~44, 45~~ 44 and 45 passing only through the second end 43 of the strap and the main part of the strap 24, whilst some of the stitching ~~44, 45~~ 44 and 45 passes through the second end part 43 of the strap, the first end part 40 of the strap and the main body of the strap. The stitching serves to embrace the elongate loop 51 of the connector 50 within the sewn strap 24.

[0070] As illustrated most clearly in Figure 15, a length of slack ~~63~~ 64 is left in the region of strap 24 extending between the first lines of stitching ~~40, 41~~ 40 and 41 and the first under-surface-slot 62 of the channel 61.

[0071] The helically-wound lengths of wire 56 serve as biasing springs to bias the mounting elements 52 towards an initial position in which the mounting elements 52 extend substantially perpendicularly to the axis of the elongate element 53. The buckle 57 initially has the position shown in Figure 15 in which the axis of the buckle 57 is substantially perpendicular to the axis of the elongate element 53. However, the buckle 57 can be moved, against the bias of the helically-wound lengths of wire 56, to the alternate position shown in ~~Figure 16~~, in which the buckle 57 is generally in alignment with the elongate element 53, extending substantially upwardly above the elongate element 53. The provision of the length of slack ~~63~~ 64 (illustrated in Figure 15) allows unhindered movement of the buckle 57 from the position illustrated in Figure 15 to the upward position ~~illustrated in Figure 16~~.

[0072] It is to be appreciated that the buckle assembly of the type described above with respect to Figures 11 to ~~46~~ 15 is again of particular use for mounting on the rear seat of a vehicle in generally the same way as the assembly of Figures 3 to 10.

~~— In the present Specification "comprises" means "includes or consists of" and~~
"comprising"